



# YOUR PASSPORT TO PACKAGING





# THE NEW BENCHMARK OF PACKAGING

# END-USE APPLICATIONS

WRAPAROUND LABELS

SHRINK SLEEVES

POUCHES & SACHETS

**BLISTERS** 

1ML

FLEXIBLE PACKAGING SPECIAL APPLICATIONS Varyflex V4 Offset is the real breakthrough in **mid-web packaging printing market**. Thanks to a newly designed **Offset print unit** featuring next-generation technologies and electronics, it provides the best performance in the production of **high-end flexible packaging**, premium labels and special applications.

It can handle several kind of substrate with the maximum flexibility and the typical reliability of OMET technology. With its **maximum mechanical speed of 400 m/min** and the combination of offset, flexo and rotogravure printing technologies, Varyflex V4 is undoubtedly the best solution for printers specialized in **high-end flexible packaging production**.

# TARGET MARKETS

HEALTHCARE & COSMETICS FOOD & BEVERAGE HOUSEHOLD INDUSTRIAL PHARMA SECURITY

### THE OFFSET UNIT

#### **INKING TRAIN**

The inking train is made of 19 rollers with automatic washing system, including 6 distributors rollers with controlled temperature and 4 form rollers on the offset plate.

#### **INK DUCT**

The ink is dosed by high-precision ink ducts with laser-carved independent sectors featuring automated remote adjustment and control.

#### **DAMPENING SYSTEM**

The dampening system features one temperature-controlled oscillating roller and provides balanced dampening on the offset plate either "mixed ink + water" or "water only", for metallic or phosphorescent inks.


#### **AUTOMATIC CLEANING SYSTEM**

The offset unit features on-the-run automatic plate cleaning system and can be equipped also with automatic blanket and impression cylinder cleaning systems.

#### **OFFSET/FLEXO CONVERSION SYSTEM**

Every offset group can be converted into flexo units with a quick and easy conversion process. Thanks to a special adaptation kit, the printing equipment is interchangeable with standard V4 flexo unit's.













### **MAIN FEATURES**

### OMET PATENT TECHNOLOGY

OMET Offset by Sleeve technology is based on a **patented design** which makes it a unique top-class solution, specifically developed with one goal: provid-ing **high quality printing** results.

#### **SOLID DESIGN**

The design of the printing section assures extreme stability at the highest speed.

- Bouncing compensation (gap)
- No vibrations
- Constant wrap of the web



#### **INDEPENDENT PRESSURE ADJUSTMENT**

Each offset printing unit features 15 motors for automatic set-up and independent pressure adjustment blanket-plate and blanket-impression cylinder.

EASY SLEEVE FORMAT CHANGE This innovative system is based on OMET patented sleeve technology, which guarantees **quick repeat changeovers and user-friendly operations**.

#### THE REVOLVER CART

The Revolver cart is a smart sleeve-holding device that facilitates sleeves changeover. It can house up to 8 sleeves and serve 3 printing units, with 2 free shafts always available.




#### **RFID SLEEVES EQUIPMENT**

Varyflex V4 Offset uses pneumo locking sleeves available with fiberglass, aluminum or carbon fiber external tube and integrated RFID identification system.

### **OFFSET CONFIGURATIONS**


#### **UV WET/WET**



Multiple-lamp drying system installed in-between multiple printing units, with UV lamps mounted on a large servo-driven chill drum. It is suitable for both Hg and LED UV lamps.




#### **UV WET/DRY**



Interdeck UV curing system with 1 lamp mounted on a servo-driven chill drum placed inside every printing unit. It is suitable for both Hg and LED UV lamps.



#### **ELECTRON BEAM WET/WET**



Electron Beam is a food compliant curing system generating very little heat for a superior film handling and high-speed production. It provides an instantaneous and complete curing even at maximum line speed, requiring lower energy than UV and thermal drying.





# IN-LINE PRINTING COMBINATION

Varyflex V4 Offset conveys all the advantages of **Varyflex multi-process concept** allowing the integration of different printing processes in-line to obtain **value-adding hybrid results**. Thanks to its modularity, the offset platform can be integrated with **flexo** (UV, water-base, solvent-base, EB) or **rotogravure** printing units, both perfect for solid printing and special effects like **Soft Touch**.

#### **HIGH-END ROTOGRAVURE**

The new rotogravure unit is specifically designed for the application of solids and special effects on **premium shrink sleeve, labels and flexible packaging**. It features **Direct Drive transmission** on the printing cylinder, with no gears and no bearings which enables high-end printing results at every run.

OMET rotogravure unit offers extreme accessibility on both sides and it is equipped with integrated chill drum and doctor blade with front and reverse printing capability.



#### **FLEXO BY SLEEVE**

The new Flexo by Sleeve concept applied on both anilox and printing plate, along with the fully Direct Drive transmission by independent motors, make it the best complementary solution in terms of **flexibility and productivity**, with no limitations in performance and quality.

OMET flexo WET/DRY unit gives the opportunity to **print on Front and Reverse** side with UV, water-base and solvent-base inks, or even **Soft Touch hybrid composition**. The flexo WET/WET configuration allows the integration of Electron Beam curing system.



FLEXO WET/WET • Electron Beam



**FLEXO WET/DRY** 

- UV Front & Reverse
- Hot Air Front & Reverse
- Soft Touch Front & Reverse

# TECHNICAL SPECIFICATIONS

# 

	670	850
Web width	670 mm (26 3/8")	850 mm (33 4/8")
Print width	660 mm (26")	840 mm (33 1/8")
Max. speed	400 m/min	
Unwinder/Rewinder	1500 mm (60")	
Infeed/Outfeed	Servo driven - Closed loop	
Trasmissione di stampa	Servo Direct Drive	
Machine and Cross register adjustment	Automatic by Vision System	
Register control	Automatic by Vision System	
AVAILABLE PRINTING TECHNOLOGIES		
Flexo UV - WB - SB - EB	16" - 32"	16" - 32"
Offset by Sleeve	16" - 32"	16" - 32"

16" - 32" 16" - 32"

16" - 32"

OMET reserves the right to change machine specifications at any time.

Rotogravure





#### OMET srl

Via Puccini, 15 23847 Molteno (LC), ITALY Tel. +39 031 0741000 www.printing.omet.com

# INNOVATION WITH PASSION

### OMET WORLDWIDE

#### OMET Americas Inc.

1850 S Elmhurst Road Mount Prospect, IL 60056 USA Tel. +1 847 621 2369 sales@ometamericasinc.com www.ometamericasinc.com

# $\bigcirc$

 $\bigcirc$ 

 $\bigcirc$ 

### OMET Ibérica I&C S.I.

Calle Provenza, 196 08036 Barcellona SPAIN Tel. +34 66 9789946 Fax +34 93 4907740 ometiberica@terra.es

#### OMET (Suzhou) Mechanical Co. Ltd

N.255 Quande Rd, Economic Development Zone 215200 Wujiang City (Jiangsu) CHINA Tel. +86 512 63033668 admin@omet.cn www.omet.cn

# $\bigcirc$

9th floor, Tower B SAS Tower

OMET India

Sector 38 Gurgaon-122001New Delhi INDIA pawandeep.sahni@ometindia.com



facebook.com/OMETSrl **f** it.linkedin.com/company/OMETSrl **in** 

youtube.com/user/OMETcompany